
Connected Lighting



14

www.anselluk.com



Powered by Casambi


OCTO IP65 Smart PIR Sensor Powered by Casambi

OCTO IP66 Smart High Bay PIR Sensor Powered by Casambi



Smart Lighting Genius

OCTO delivers the complete smart lighting package to transform the efficiency and ambience of commercial and residential spaces, with an easy-to-use wireless system that gives complete control of the luminaries via an intuitive app and smart accessories. Utilising Connected by WiZ, Casambi and MyMesh technology, OCTO offers a comprehensive range of features that interact flawlessly with your smart device.




Please note that the various technologies we utilise as part of the OCTO solution require more than one App to operate them. Find out more about integrating technologies using our 'OCTO Gateway' (featured on p61)

The OCTO Solution

Supporting a range of requirements, from residential applications requiring voice control and commercial buildings that prioritise energy saving, to a warehouse that requires space optimisation and efficiency dashboard data... and much more!

With our continuous research, development and innovation, OCTO is constantly evolving to ensure we can offer revolutionary, forward-thinking solutions for all our customers.





CPD

We offer RIBA and Engineers Ireland accredited CPD training sessions. Learn about the fundamentals of smart lighting and how it can offer many benefits to a great number of applications. The CPD has been designed to provide guidance for professionals on the benefits of smart lighting and offers an understanding of the different technologies available.

Interested in learning more?

Get in touch here cpd@anselluk.com



A Guide to our OCTO product logos

A

We want to make choosing the right OCTO product a straightforward process, so we have introduced these logos on our product pages to help you pick the perfect solution for you smart lighting needs.

Connected by

18

OCTO Embedded WiZ Connected



WiZ

These products have WiZ technology embedded and can be instantly paired




OCTO Compatible WiZ Connected



WiZ

These products are compatible with an OCTO Connected by WiZ Product and can be converted into a smart product




A

OCTO Enabled WiZ Connected

OCTO Connected by WiZ is the perfect solution for a residential or small-scale commercial smart lighting projects. Take advantage of full voice control and WiFi/Bluetooth hybrid technology, with 16 million colours and 64,000 shades of white.

The WiZ app offers multi-user and muti-location options, making it suitable for both new and existing homes. The WiZ technology is built into the lighting fixtures meaning no hubs or additional wiring required. Simply turn on, pair up and you're good to go.



- Enjoy seamless pairing using WiFI and Bluetooth hybrid technology to support connecting to your WiFi router
- Select how you control your lights, with your smartphone, remote, motion sensors, existing wall switches or even your voice as options!
- Control your lights when you are home or away.
- Improve your wellbeing with Human Centric Lighting using the OCTO Connected by WiZ 'Circadian Rhythm', featuring pre-set smooth light transitions or personalise with the 'My Rhythm' features.
- Utilise schedules to automate your OCTO Connected by WiZ lights to fit your daily routines and save energy costs.
- Harness the power of other major connected ecosystems with easy integrations through the WiZ cloud.
- Protect your personal security via anonymous sign in and encrypted cloud connections.

21



Tum your lights on in your home from your office and vice versa. You can even control your WiZ locations from as far away as the moon. As long as you have got access to the WiZ Cloud (via WiFi or mobile data) you can do what you want to do with your lights – even when you are not physically there.

Each WiZ light has its own brain – a 32-bit MCU chip with WiFi – for smarter automation, as our lights are directly, constantly and reliably connected to the cloud for up-todate preferences and settings without any dependency on a hub or bridge.

Multiple Users

- We have a powerful multi-user system with three different access right tiers over multiple WiZ locations:
- Owners can change settings and control the lights in all their WiZ locations using internet connectivity or mobile data.
- Guests can enjoy control over lights when they are on the same Wifi network as the OCTO Connected by WiZ home they want to control – but they will not be allowed to change any settings.
- Temporary guests have the same permissions as ordinary guests but they will lose access after a certain time period that you get to set for them each one can be different!


All product names, logos and brands are property of their respective owners. Amazon, Alexa and all related logos are trademarks of Amazon. com Inc or it's affiliates. Google Assistant, the Google Assistant logo, Google Play and the Google Play logo are trademarks of Google LLC. The Apple logo is a trademark of Apple Inc., registered in the U.S. and other countries and regions. App Store is a service mark of Apple Inc.

A

OCTO GU10 Smart Lamp Connected by WiZ



- Tunable white and RGB tunable white GU10 smart lamp suitable for residential and small-scale commercial applications
- Bluetooth and WiFi enabled smart lamp; connects directly to your existing WiFi
- Commissioned via WiZ App
- Voice activated compatibility; offers hands-free controls
- Fully dimmable from 10% to 100%
- RGB and Tunable white for total colour and comfort (AOCTOW/GU10LED/RGBTW only)
- Tunable white between 2700K 6500K
- Group, scene, holiday and timer settings achieved via WiZ App
- Suitable for any GU10 compatible product Please check lamp size to ensure compatibility











INPUT	HERTZ	TEMP	LIFETIME (HRS)	CRI	BEAM ANGLE	IP
220/240V	50/60Hz	-20°C to 45°C	15,000	Ra 90	36 [°]	IP20
CODE		CRIPTION	WATTAGE	CCT	LUMENS	TRADE
AOCTOW/GU10LED/RGBTW	I	RGBTW	4 71 11	2200K-6500K and RGB	4001	£30.75
AOCTOW/GU10LED/TW	Tun	able White	4.7W	2700K-6500K	400lm	£25.65

OCTO A60 Tunable Smart Lamp **Connected by WiZ**

Voice Control

118

Ø60

Ø60

- Tunable white A60 smart lamp suitable for residential and small scale commercial applications .
- . Bluetooth and WiFi enabled smart lamp; connects directly to your existing WiFi
- Commissioned via WiZ App .
- Voice activated compatibility; offers hands-free controls .
- Fully dimmable from 10% to 100% .
- Tunable white between 2700K 6500K
- E27 and B22 base options available
- Group, scene, holiday and timer settings achieved via WiZ App
- Suitable for indoor applications in dry rooms, professional use in public buildings and outdoor use in specially shielded luminaires



INPUT	HERTZ	TEMP	LIFETIME (HRS)	CRI	IP
220/240V	50/60Hz	-20°C to 45°C	25,000	Ra 90	IP20
CODE	DESCRIPTION	WATTAGE	CCT	LUMENS	TRADE
AOCTOW/A60LED/TW/B22	A60 - Tunable White - E	322 8W	2700K-6500K	806lm	£45.60
AOCTOW/A60LED/TW/E27	A60 - Tunable White - E		2700K-0000K	80600	£45.60



116




Connected by WiZ



Control

- RGB tunable white A60 smart lamp suitable for residential and small-scale commercial applications .
- . Bluetooth and WiFi enabled smart lamp; connects directly to your existing WiFi
- Commissioned via WiZ App .
- Voice activated compatibility; offers hands-free controls .
- RGB and Tunable white for total colour and comfort •
- Fully dimmable from 10% to 100% .
- Group, scene, holiday and timer settings achieved via WiZ App
 - Suitable for indoor applications in dry rooms, professional use in public buildings and outdoor use in specially shielded luminaires






INPUT	HERTZ	TEMP	LIFETIME (HRS)	CRI	IP
220/240V	50/60Hz	-20°C to 45°C	25,000	Ra 90	IP20
CODE	DESCRIPTION	WATTAGE	CCT	LUMENS	TRADE
AOCTOW/A60LED/RGBTW/B22	A60 RGBTW - B22	0.11/	2700K-6500K and RGB	906lm	£57.00
AOCTOW/A60LED/RGBTW/E27	A60 RGBTW - E27	8W	2700K-0000K and Rub	806lm	£57.00

OCTO G95 RGBTW Smart Lamp 🛶 😭 🔊 Connected by WiZ

- RGB tunable white G95 smart lamp suitable for residential and small-scale commercial applications
- Bluetooth and WiFi enabled smart lamp; connects directly to your existing WiFi
- Commissioned via WiZ App
- Voice activated compatibility; offers hands-free controls
- RGB and Tunable white for total colour and comfort
- Fully dimmable from 10% to 100%
- Group, scene, holiday and timer settings achieved via WiZ App
- Suitable for indoor applications in dry rooms, professional use in public buildings and outdoor use in specially shielded luminaires





INPUT	HERTZ	TEMP		LIFETIME (HRS)	CRI	IP
220/240V	50/60Hz	-20°C to 45°C		25,000	Ra 90	IP20
CODE		DESCRIPTION	WATTAGE	CCT	LUMENS	TRADE
AOCTOW/G95LED/RGBTW/B22		G95 RGBTW - B22	11W	2700K-6500K and RGB	1055	£68.50
AOCTOW/G95LED/RGBTW/E27		G95 RGBTW - E27	1 I VV	2700K-0000K and KGB	1055lm	£68.50

Voice Control

RGBTW Smart Lamp Connected OCTO C37 Tunable White and by WiZ



Ø39

RGBTW

110

- Tunable white and RGB tunable white C37 smart lamp suitable for residential and small-scale commercial applications
- Bluetooth and WiFi enabled smart lamp; connects directly to your existing WiFi
- Commissioned via WiZ App
- Voice activated compatibility; offers hands-free controls .
- Fully dimmable from 10% to 100% .
- Group, scene, holiday and timer settings achieved via WiZ App .
- Suitable for indoor applications in dry rooms, professional use in public buildings and outdoor use in specially shielded luminaires





Control

Ø39

ww






INPUT	HERTZ	TEMP	LIFETIME (HRS)	CRI	IP
220/240V	50/60Hz	-20°C to 45°C	15,000	Ra 90	IP20
CODE	DESCRIPTION	WATTAGE	CCT	LUMENS	TRADE
A0CTOW/C37/RGBTW/E14	C37 RGBTW - E14	4.9W	2200K-6500K and RGB	470lm	£42.05
A0CTOW/C37/WW/E14	C37 Warm White - E14	4.9W	2700K	47 UITI	£32.40

OCTO A60 Tunable White Frosted Smart Lamp Connected by WiZ

- Tunable White A60 smart lamp suitable for residential and small-scale commercial applications
- Bluetooth and WiFi enabled smart lamp; connects directly to your existing WiFi
- Commissioned via WiZ App
- Voice activated compatibility; offers hands-free controls
- A60 is comparable with 60W incandescent lamp
- Fully dimmable from 10% to 100%
- Tunable white between 2700K 6500K
- Group, scene, holiday and timer settings achieved via WiZ App
- Suitable for indoor applications in dry rooms, professional use in public buildings and outdoor use in specially shielded luminaires





INPUT	HERTZ	TEMP	LIFETIME (HRS)	CRI	IP
220/240V	50/60Hz	-20°C to 45°C	15,000	Ra 90	IP20
CODE	DESCRIPTION	WATTAGE	CCT	LUMENS	TRADE
AOCTOW/A60/TW/FR/E27	A60 - Tunable White - E27	7W	2700K-6500K	806lm	£34.10



OCTO A60 Tunable White Smart Filament Lamp Connected by WiZ




Control

mbeddec

ViZ

- Tunable white A60 smart filament lamp suitable for residential and small-scale commercial applications
- Bluetooth and WiFi enabled smart lamp; connects directly to your existing WiFi
- Commissioned via WiZ App
- Voice activated compatibility; offers hands-free controls
- Vintage amber and clear filament lamp designs
- A60 is comparable with 60W incandescent lamp
- Fully dimmable from 10% to 100%
- Tunable white between 2700K 6500K
- Group, scene, holiday and timer settings achieved via WiZ App
- Suitable for indoor applications in dry rooms, professional use in public buildings and outdoor use in specially shielded luminaires





INPUT	HERTZ	TEMP	LIFETIME		CRI	
220/240V	50/60Hz	50/60Hz -20°C to 45°C		0	Ra 90	IP20
CODE	Di	ESCRIPTION	WATTAGE	CCT	LUMENS	TRADE
AOCTOW/A60/TW/AMB/E27	A60	- Amber - E27	7W	00001/ 50001/	0.401	£37.85
AOCTOW/A60/TW/AMB/B22	A60	- Amber - B22	7 VV	2000K-5000K	640lm	£37.85
AOCTOW/A60/TW/CL/E27	A60) - Clear - E27	7.0		0001	£37.20
A0CTOW/A60/TW/CL/B22	A60) - Clear - B22	7W	2700K-6500K	806lm	£37.20



- Tunable white ST64 smart filament lamp suitable for residential and small-scale commercial applications
- Bluetooth and WiFi enabled smart lamp; connects directly to your existing WiFi
- Commissioned via WiZ App
- · Voice activated compatibility; offers hands-free controls
- Vintage amber and clear filament ST64 lamp designs
- Comparable with 60W incandescent lamp
- Fully dimmable from 10% to 100%
- Tunable white between 2700K 6500K
- Group, scene, holiday and timer settings achieved via WiZ App
- Suitable for indoor applications in dry rooms, professional use in public buildings and outdoor use in specially shielded luminaires



INPUT	HERTZ	TEMP	LIFETIME (HRS)	CRI	IP
220/240V	50/60Hz	-20°C to 45°C	15,000	Ra 90	IP20
CODE	DESCRIPTION	WATTAGE	CCT	LUMENS	TRADE
A0CTOW/ST64/TW/AMB/E27	ST64 - Amber - E27	71.07		640lm	£39.30
AOCTOW/ST64/TW/CL/E27	ST64 - Clear - E27	7W	2000K-5000K	806lm	£38.25




Ø64

Control

OCTO G95 Tunable White Smart Filament Lamp Connected by WiZ



- Tunable white G95 smart filament lamp suitable for residential and small-scale commercial applications
- Bluetooth and WiFi enabled smart lamp; connects directly to your existing WiFi
- Commissioned via WiZ App
- Voice activated compatibility; offers hands-free controls
- Vintage amber and clear filament G95 lamp designs
- Comparable with 75W incandescent lamp
- Fully dimmable from 10% to 100%
- Tunable white between 2700K 6500K
- Group, scene, holiday and timer settings achieved via WiZ App
- Suitable for indoor applications in dry rooms, professional use in public buildings and outdoor use in specially shielded luminaires



Control





INPUT	HERTZ	TEMP	LIFETIME (HRS)	CRI	IP
220/240V	50/60Hz	-20°C to 45°C	15,000	Ra 90	IP20
CODE	DESCRIPTION	WATTAGE	CCT	LUMENS	TRADE
AOCTOW/G95/TW/AMB/E27	G95 - Amber - E27	7W	2000K-5000K	640lm	£45.90
AOCTOW/G95/TW/CL/E27	G95 - Clear - E27	7 VV	2000K-3000K	806lm	£44.85

OCTO C37 Tunable White Smart Filament Lamp Connected by WiZ



- Tunable white C37 smart filament lamp suitable for residential and small-scale commercial applications
- Bluetooth and WiFi enabled smart lamp; connects directly to your existing WiFi
- Commissioned via WiZ App
- Voice activated compatibility; offers hands-free controls
- Vintage amber and clear filament candle lamp designs
- Fully dimmable from 10% to 100%
- Tunable white between 2700K 6500K
- Group, scene, holiday and timer settings achieved via WiZ App
- Suitable for indoor applications in dry rooms, professional use in public buildings and outdoor use in specially shielded luminaires





INPUT	HERTZ	TEMP	LIFETIME (HRS)	CRI	IP
220/240V	50/60Hz	-20°C to 45°C	15,000	Ra 90	IP20
CODE	DESCRIPTION	WATTA	GE CCT	LUMENS	TRADE
AOCTOW/C37/TW/AMB/E14	C37 - Amber - E14		00001/ 50001/	370lm	£36.95
A0CTOW/C37/TW/CL/E14	C37 - Clear - E14	4.9W	2000K-5000K	470lm	£36.05

31

Warrington: +44 (0) 1942 433333 Belfast: +44 (0) 2890 773750

- Smart remote control suitable for residential and small-scale commercial applications
- Multifunctional WiFi enabled smart remote control lets you have quick and easy control of your OCTO Connected by WiZ lights
- Simple and quick controls; on/off, dimming, night light and choose from different scenes
- Compatible with all other OCTO Connected by WiZ devices
- Works without WiFi
- Range Up to 15 metres



157

34

0 0

0

00

00

WiZ







CODE	DESCRIPTION	P



Complete Control

in one click Instant switching between Preset light modes and Preset Dynamic light modes 谢 🗱 🦚 🖧 🧊 🎲 🖏 👘 🍪 🚼 🙇 💭 🛶 🕘 🐮 🇯 0

Night Light Mode


Dim lights up and down

OCTO Indoor Controller Connected by WiZ

- Bluetooth and Wifi enabled smart controllers for use with LED strip suitable for residential and small-scale commercial applications
- Commissioned via WiZ App
- Voice activated compatibility; offers hands-free controls
- 12-24V Dimmable, RGB and tunable white versions; perfect for LED strip (maximum 7.5A)
- 220-240V Dimmable; perfect for triac dimmable downlights and other LED luminaires and LED light sources (maximum 150W)
- 1-10V Dimmable version for compatible analogue LED luminaires (maximum 300W)
- Group, scene, holiday and timer settings achieved via WiZ App







Connected by



CODE	DESCRIPTION	MIN VOLTAGE	MAX VOLTAGE	IP	CLASS	TRADE
AOCTOW/12-24V/DIM	12-24V Dimmable Controller					£79.00
AOCTOW/12-24V/TW	12-24V Tunable White Controller	12V	24V	IP20	2	£79.00
AOCTOW/12-24V/RGBTW	12-24V RGBTW Controller					£79.50
AOCTOW/220-240V/DIM	220-240V Phase-cut Dimmable Controller	2201/	2401/		0	£79.00
AOCTOW/1-10V/DIM	220-240V 1-10V Dimmable Controller	220V	240V	IP20	2	£79.00


34

www.anselluk.com

OCTO Wireless Smart Plug Connected by WiZ

- WiFi enabled smart plug for residential and small scale commercial applications
- Make any socket smart with this OCTO Smart Plug Connected by WiZ
- Control your lights and electronic devices from anywhere
- 13A Rated
- Integrated manual on/off button
- Program schedules and timers via WiZ app
- Provides safety, security and energy saving benefits
- Voice control with Alexa, Hey Google and Siri Shortcuts














CODE	DESCRIPTION	IP	TRADE
AOCTOW/SP	Smart Plug	IP20	£28.50



OCTO Smart PIR Sensor Connected by WiZ

- Internal WiFi enabled PIR sensor suitable for residential and small-scale commercial applications
- Compatible with all other OCTO Connected by WiZ devices
- Infrared PIR detector and photocell
- Detection range strength: 1) Strong detection zone i.e. person moving arm or walking towards PIR 2) Secondary detection zone i.e. person walking perpendicular to PIR
- 1 year battery (on assumption 50 actions per day, battery capacity 2800 mAh)
 - Battery powered using 2 x AA batteries (not supplied)
















Ceiling Installation











CODE	DESCRIPTION	CLASS		TRADE
AOCTOW/PIR-S	Smart PIR Sensor - Internal	3	IP20	£41.60


36

www.anselluk.com

OCTO Outdoor Smart PIR Sensor Connected by WiZ

- IP65 external Wifi enabled PIR sensor suitable for residential and small-scale commercial applications
- Compatible with all other OCTO Connected by WiZ devices
- Infrared PIR detector and photocell
- Detection range strength: 1) Strong detection zone i.e. person moving arm or walking towards PIR 2) Secondary detection zone i.e. person walking perpendicular to PIR
- Typical battery lifetime 1 year (on assumption 50 actions per day, battery capacity 2800 mAh)
- Battery powered using 2 x AA batteries (not supplied)
- Please consider WiFi signal strength for this product

















CODE	DESCRIPTION	IP	IK	TRADE
AOCTOW/B/PIR/IP65-S	Smart PIR Sensor - External	IP65	08	£322.00



OCTO Venom RGBW Flexible Strip Kit Connected by WiZ



Voice Control

- RGBTW smart flexible LED strip kit suitable for residential and small-scale commercial applications
- Bluetooth and WiFi enabled smart strip; connects directly to your existing WiFi
- Commissioned via WiZ App
- Voice activated compatibility; offers hands-free controls
- RGB and Tunable white for total colour and comfort
- Fully dimmable from 10% to 100%
- 2m starter kit with additional 1m extender kit options available (up to 10m maximum total LED strip length)
- Cutting points every 200mm (only if required)
- Group, scene, holiday and timer settings achieved via WiZ App



INPUT	HERTZ	TEMP	LIFETIME (HRS)	CRI	CLASS	IP
220/240V	50/60Hz	-10℃ - 45℃	15,000	Ra 80	2	IP20
CODE		DESCRIPTION	WATTAGE	CCT	LUMENS	TRADE
AOCTOW/VENOM/KIT2M/RGBT	W	RGBTW - 2m	20W		2000lm	£130.00
AOCTOW/VENOM/EXT1M/RGB	TW RGBTV	V - Extension Kit 1m	11W	2700K-6500K (RGB)	1000lm	£48.75

39

Warrington: +44 (0) 1942 433333 Belfast: +44 (0) 2890 773750

OCTO Prism Pro Fire Rated Downlight Connected by WiZ



- Tunable between 2700K 6000K via WiZ App and voice control
- IP65 dimmable LED WiZ enabled tunable white Fire Rated Downlight suitable for residential and hospitality applications
- Supplied with matt white bezel as standard
- Remote driver with 2x1.5mm² + CPC loop-in, loop-out colour coded push fit piano terminals provide an easy and efficient installation
- Detachable LED driver for fast fix install
- Low profile design and remote driver allow installation into shallow ceiling voids
- Fully tested for 30, 60 and 90 minute ceiling types to meet Part B of Building Regulations
- Fully tested to meet Part C (moisture), Part E (acoustic) and Part L (energy) of Building Regulations
- Wide 60° beam angle for increased light distribution



INPUT	HERTZ	TEMP	LIFETIME (H	irs) cr	I SDCM	BEAM ANGLE	CLASS	IP
230V	50/60Hz	-5°C to 25°C	L70 60,00)0 Ra 8	6	60°	1	IP65
CODE	DES	CRIPTION	WATTAGE	CCT	LUMENS		LM/W	TRADE
APRILEDP/OCTOW	Tuna	able White	7W	2700K-6000K	573lm (2700K) - 547lm (60	100K) 82lm (2700	0K) - 78lm (6000K)	£92.00
CODE (ACCESSORIES)		DESCRIPTION		TRADE	CODE (ACCESSORIES)	DESCRI	PTION	TRADE
APRILEDPBZ/CH	Cł	nrome Trim Bezel		£4.15	APRILEDP/CP/MW	Converter Kit	Matt White	£11.05
APRILEDPBZ/SC	Satin	Chrome Trim Bezel		£4.15	APRILEDP/CP/CH	Converter K	(it Chrome	£13.15
APRILEDPBZ/BLK	Ma	tt Black Trim Bezel		£4.15	APRILEDP/CP/SC	Converter Kit S	Satin Chrome	£13.15
ACFLP/3	LED Em	ergency Lighting Pack		£131.00	APRILEDP/CP/BLK	Converter	Kit Black	£13.15

0







WiFi and Bluetooth

Enjoy seamless pairing using WiFl and Bluetooth hybrid technology to support connecting to your WiFi router

Advance Voice Control

Full voice control with smart speakers and now with Google Assistant and Siri Shortcuts on iOS 12, have full control of your lights by talking to any smartphone.

No Hub Needed


32-bit MCU chip provides smarter automation, as WiZ lighting is directly, constantly and reliably connected to the cloud there is no dependency on a hub or bridge.



OCTO Prism Pro Anti-Glare FRD Connected by WiZ



- IP65 Dimmable LED WiZ enabled tunable white Fire Rated Anti-Glare Downlight suitable for residential and commercial applications
- Supplied with matt white bezel as standard
- Anti-glare design to create visual comfort •
- Tunable between 2700K 6000K via Wiz App and voice control .
- Remote driver with 2x1.5mm² + CPC loop-in, loop-out colour coded push fit piano . terminals provide an easy and efficient installation
- . Detachable LED driver for fast fix install
- Low profile design and remote driver allow installation into shallow ceiling voids .
- Fully tested for 30, 60 and 90 minute ceiling types to meet Part B of Building Regulations .
- Fully tested to meet Part C (moisture), Part E (acoustic) and Part L (energy) of Building Regulations





black insert fitted as standard

with matt black insert accessory

accessory


INPUT	HERTZ	TEMP	LIFETI	ME (HRS)	CRI	SDCM	BEAM ANGLE	CLASS		
230V	50/60Hz	-5°C to 25°C	L70	33,000	Ra 80	6	50°	1		IP65
CODE		SCRIPTION V	VATTAGE	CCT		LUMENS	LM/W			TRADE
APRILEDP/AG/OCTOW	Tur	able White	8W	2700K - 6000K	402lm (2	2700K) - 410lm (6000K)	50lm (2700K and (5000K)	18	£88.50
								* U(GR Value ba	ased on (4H - 8H,
CODE (ACCESSORIES)		DESCRIPTIO	N	TRADE	C	DDE (ACCESSORIES)	DESCRIP	TION		TRADE
APRILEDPBZ/AG/WW	Wh	ite Trim Bezel with V	Vhite Insert	£6.90	A	CFLP/3	LED Emergency I	lighting Pack		£131.00
APRILEDPBZ/AG/BB	Matt Bla	ick Trim Bezel with M	Aatt Black Ins	sert £6.90						
APRILEDPBZ/AG/CHB	Chrom	e Trim Bezel with M	att Black Inse	ert £6.90						
APRILEDPBZ/AG/SCB	Satin Chro	ome Trim Bezel with	Matt Black I	nsert £6.90						



OCTO Gamma Mini Connected by WiZ



- Ultra slim modern WiZ enabled polycarbonate wall/ceiling light suitable for education and residential applications and ancillary areas
- Matt white finish to body and diffuser with optional chrome trim ring
- Rear fixing bracket and terminal housing for ease of installation
- Tunable between 2700K 6500K via Wiz App and voice control
- IP54 rating and suitable for bathroom use
- Dimmable via WiZ App







Connected by



AMGAMLED/OCTOW



Chrome Trim Ring Fitted

INPUT	HERTZ	TEMP	LIFETIME (HRS)	CRI	SDCM	BEAM ANGLE	CLASS		IK
230V	50Hz	-5°C to 35°C	L70 54,000	Ra 80	6	110°	2	IP54	IK09
CODE		DESCRIPTION	WATTAGE	CCT		LUMENS		M/W	TRADE
AMGAMLED/0CT	TOW	Tunable White	10W	2700K-6500K	750lm (27	700K) - 830lm (6500K)	77lm (2700K) - 86lm (6500K)	£93.50
CODE (ACCESSO	RIES)			DESC	RIPTION				TRADE
AMGAMLEDBZ/0	СН			Chrome	e Trim Ring				£6.45


OCTO Gamma Connected by WiZ



 Ultra slim modern WiZ enabled polycarbonate wall/ceiling light suitable for education and residential applications and ancillary areas

- Matt white finish to body and diffuser with optional chrome trim ring
- Rear fixing bracket and terminal housing for ease of installation
- Tunable between 2700K 6500K via Wiz App and voice control
- IP54 rating and suitable for bathroom use
- Dimmable via WiZ App

TUNABLE







Connected by







Chrome Trim Ring Fitted

INPUT	HERTZ	TEMP	LIFETIME (HRS)	CRI	SDCM	BEAM ANGLE	CLASS		IK
230V	50Hz	-5°C to 35°C	L70 54,000	Ra 80	6	110°	2	IP54	IK09
CODE		DESCRIPTION	WATTAGE	CCT		LUMENS		.M/W	TRADE
AGAMLED/OCTO	N	Tunable White	18W	2700K-6500K	1500lm (270	IOK) - 1620lm (6500K)	82lm (2700k	() - 90lm (6500K)	£156.00
CODE (ACCESSOR					SCRIPTION				TRADE
AGAMLEDBZ/CH				Chron	ne Trim Ring				£10.10





46

OCTO Disco Slim Connected by WiZ



- WiZ embedded slim and modern wall or ceiling light suitable for education and residential applications and ancillary areas
- All polycarbonate construction with opal diffuser and white trim ring with optional chrome or graphite ring
- Tunable between 2700K 6500K via WiZ App and voice control
- Instant light output and unlimited switching















fitted with chrome trim ring


fitted with graphite trim ring

INPUT	HERTZ	TEMP	LIFETIME (HRS)	CRI	SDCM	BEAM ANGLE	CLASS		IK
230V	50Hz	-10°C to 40°C	L70 36,000	Ra 80	6	110 [°]	2	IP65	08
CODE		DESCRIPTION	WATTAGE	CCT		LUMENS		LM/W	TRADE
ADSILED1/0CT	OW	Tunable White	8W	2700K-6500K	. 720im (2	2700K) - 708im (6500K)	90lm (270	0K) - 89lm (6500K)	£244.00
ADSILED2/0CT	OW	Tunable White	11W	2700K-6500K	. 1150im (2	2700K) - 1153lm (6500K)	105lm (270	10K) - 112lm (6500K)	£271.00
CODE (ACCESS	ORIES)	DESCRIPTION		TRADE	CODE (ACCES	SORIES)	DESCRIPTIO	N	TRADE
ADSILED/1BZ/C	H	Chrome Trim Ring (8W	I)	£10.90	ADSILED/2BZ/	CH C	hrome Trim Ring	(11W)	£11.75
ADSILED/1BZ/G	iR	Graphite Trim Ring (8V	V)	£10.90	ADSILED/2BZ/	'GR G	raphite Trim Ring	(11W)	£11.75

OCTO Astro Connected by WiZ



- WiZ embedded all polycarbonate multi-purpose LED square bulkhead suitable for ancillary areas and industrial applications
- Push fit feed-in, feed-out terminals for speed and ease of installation
- Tunable between 2700K 6500K via WiZ App and voice control
- Supplied c/w optional trim attachment which provides a more commercially aesthetic appearance
- Unique Visiluxe diffuser allows 90% light transmission from LED source for increased performance
- Instant light output and unlimited switching






Black (Fitted with Trim Attachment) White (Fitted with Trim Attachment)

INPUT	HERTZ	TEMP	LIFETIME (HRS)	CRI	SDCM	BEAM ANGLE	CLASS		IK
230V	50Hz	-10°C to 40°C	L70 36,000	Ra 80	6	115 [°]	2	IP65	08
CODE		DESCRIPTION	WATTAGE	CCT		UMENS		LM/W	TRADE
AALED1/BV/0CT	row	Tunable White - Black	8W	2700K-6500K	700lm (0700	014 700lm (6E0014	01lm /0700	K) - 90lm (6500K)	£294.00
AALED1/WV/0C	TOW	Tunable White - White	8W	27006-00006	730111 (2700)K) - 720lm (6500K)	91111 (2700	n) - 90111 (0000n)	£294.00
AALED2/BV/0CT	гоw	Tunable White - Black	11W	2700K-6500K	1150km (0700	1170m (CE00K)	10Elm /0700	100lm (6500l/)	£328.50
AALED2/WV/0C	TOW	Tunable White - White	11W	27008-00006	1130111 (2700)K) - 1170lm (6500K)	100111 (2700	K) - 106lm (6500K)	£328.50

OCTO Delta Connected by WiZ



- WiZ embedded all polycarbonate multi-purpose LED round bulkhead suitable for ancillary areas and industrial applications
- Push fit feed-in, feed-out terminals for speed and ease of installation
- Tunable between 2700K 6500K via WiZ App and voice control
- Supplied c/w optional trim attachment which provides a more commercially aesthetic appearance
- Unique Visiluxe diffuser allows 90% light transmission from LED source for increased performance
- Instant light output and unlimited switching





Black

White

(Fitted with Trim Attachment)










Black (Fitted with Louvred Bezel Trim)

INPUT	HERTZ	TEMP	LIFETIME (HRS)	CRI	SDCM	BEAM ANGLE	CLASS	IP	IK
230V	50Hz	-10°C to 40°C	L70 36,000	Ra 80	6	115 [°]	2	IP65	IK08
CODE		DESCRIPTION	WATTAGE	CCT	LU	MENS	L	M/W	TRADE
ADLED1/BV/0CT	OW	Tunable White - Black	8W	2700K-6500K	700lm /9700l/) - 712lm (6500K)	97 Elm /9700	<) - 89lm (6500K)	£290.50
ADLED1/WV/0CT	WO	Tunable White - White	8W	27000-00000	700111(2700K) = 7 12111 (0000K)	07.3IIII (2700r	y - 09111 (0000K)	£290.50
ADLED2/BV/0CT	W	Tunable White - Black	8W	2700K-6500K	1100lm (9700l/) - 1180lm (6500K)	100lm (9700l/	100m (CE001/)	£319.50
ADLED2/WV/0CT	WO	Tunable White - White	11W	27000-00000	1100111(2700K) - 1100(111(0000K)	100111 (2700K)) - 108lm (6500K)	£319.50
CODE (ACCESSO	RIES)	DESCRIPTION		TRADE	CODE (ACCES	SORIES)	DESCRIPTI	N	TRADE
ADLED2/BZ/EYE/B	E	Black Eyelid Bezel Trim (11\	N Only)	£19.05	ADLED2/BZ/G	RILL/B Bla	ck Louvred Bezel Trin	n (11W Only)	£19.05
ADLED2/BZ/EYE/W	١	White Eyelid Bezel Trim (11)	N Only)	£17.10	ADLED2/BZ/G	RILL/W Wh	ite Louvred Bezel Trin	n (11W Only)	£17.10

Reef Directional Wall Light Connected by WiZ

- . Durable WiZ embedded outdoor directional wall light suitable for residential and hospitality applications
- Installation in either upward or downward orientation .
- Choice of matt white or black finishes •
- Polycarbonate construction ideal for coastal applications .
- Refined durable finish suitable for the challenging environments . with adverse weather conditions
- Tunable between 2700K 6500K via WiZ App and voice control
- Unique lockable installation base plate with push fit loop-in loop-out terminals for ease of installation
- Please consider WiFi signal strength for this product



Ś

3YR

80 103

Voice Control









Black

Unique Click and Lock Mounting Bracket





White

INPUT	HERTZ	TEMP	LIFETIME (HRS)	CRI	SDCM	BEAM ANGL	e class	IP
230V	50Hz	-20°C to 40°C	L80 54,000	Ra 80	6	90°	2	IP65
CODE		DESCRIPTION	WATTAGE	CCT	LUMENS		LM/W	TRADE
AREELEDWLD/0C	TOW	Tunable White - Black	< 6W	22001 65001	450km (0700k) 500k	m (CE0014 7	70lm (0700l/) 00lm (6500l/)	£95.00
AREELEDWLD/WH/	OCTOW	Tunable White - White		2700K-6500K	450lm (2700K) - 500lr	II (AUUCO) /	'Olm (2700K) - 80lm (6500K)	£95.00

Reef Bi-Directional Wall Light

- Durable WiZ embedded outdoor bi-directional wall light suitable for residential and hospitality applications
- Polycarbonate construction ideal for coastal applications
- Choice of matt white or black finishes
- Polycarbonate construction ideal for coastal applications
- Refined durable finish suitable for the challenging environments with adverse weather conditions
- Tunable between 2700K 6500K via WiZ App and voice control
- Unique lockable installation base plate with push fit loop-in loop-out terminals for ease of installation
- Please consider WiFi signal strength for this product

TUNABLE



Black


Unique Click and Lock Mounting Bracket





White

INPUT	HERTZ	TEMP	LIFETIME (HRS)	CRI	SDCM	BEAM ANGLI	e class	IP
220-240V	50Hz	-20°C to 40°C	L70 54,000	Ra 80	6	90°	2	IP65
CODE		DESCRIPTION	WATTAGE	CCT	LUMENS		LM/W	TRADE
AREELEDWL/OCTO	W	Tunable White - Blac	k 10W	0700K 6500K	700lm (0700l/) 00E		70lm (070014 00lm (650014	£95.00
AREELEDWL/WH/OCTOW		Tunable White - Whit		2700K-6500K	780lm (2700K) - 825	IIII (0000K)	78lm (2700K) - 82lm (6500K)	£95.00



Voice Control

ĺ






CONNECTED LIGHTING



Leo Polycarbonate Half Lantern Connected by WiZ



- Modern styled WiZ embedded half lantern with polycarbonate construction suitable for commercial and residential applications
- White reflector with clear polycarbonate diffuser
- Polycarbonate construction is ideal for coastal applications
- Tunable between 2700K 6500K via WiZ App and voice control
- Please consider WiFi signal strength for this product











INPUT	HERTZ	TEMP	LIFETIME (HRS)	CRI	SDCM	BEAM ANGLE	CLASS		IK
230V	50/60Hz	-10°C to 40°C	L70 36,000	Ra 80	6	130 [°]	2	IP65	06
CODE		DESCRIPTION	WATTAGE	CCT		LUMENS	L	M/W	TRADE
ALEOLED/HL/	OCTOW	Tunable White	9W	2700K-6500K	759lm (270	0K) - 755lm (6500K)	41lm (2700K) - 40lm (6500K)	£125.50

Leo Polycarbonate Lantern Connected by WiZ

Modern styled WiZ embedded wall lantern with polycarbonate construction

suitable for commercial and residential applications White reflector with clear polycarbonate diffuser

Polycarbonate construction is ideal for coastal applications

Please consider WiFi signal strength for this product

Tunable between 2700K - 6500K via WiZ App and voice control

.

.

.



ğ

126





ر الألال
Embedded



0001/ 5/				CRI	SDCM	BEAM ANGLE	CLASS		IK
230V 50	0/60Hz -1	0°C to 40°C	L70 36,000	Ra 80	6	130 [°]	2	IP65	06
CODE		DESCRIPTION	WATTAGE	CCT	LUN		LM/W		TRADE
ALEOLED/WL/OCTOW	T	Funable White	9W 2	2700K-6500K	474lm (2700K)	- 446lm (6500K)	52lm (2700K) - 56li	m (6500K)	£130.00



Leo Polycarbonate Bollard **Connected by WiZ**



- Modern styled WiZ embedded bollard with polycarbonate construction suitable for residential and hospitality applications
- White reflector with clear polycarbonate diffuser

TUNABLE WHITE

230V

ALEOLED/045/GR/0CTOW

ALEOLED/075/GR/0CTOW

ALEOLED/100/GR/OCTOW

50/60Hz

-10°C to 40°C

DESCRIPTION

Tunable White - 450mm

Tunable White - 750mm

Tunable White - 1000mm

- Polycarbonate construction is ideal for coastal applications
- Supplied c/w root mounting kit, can be surface mounted with rawbolts
- . Tunable between 2700K - 6500K via WiZ App and voice control
- Please consider WiFi signal strength for this product







L70 36,000

9W

11W

Ra 80

2700K-6500K

6

560lm (2700K) - 572lm (6500K)

836lm (2700K) - 852lm (6500K)

130[°]

1

61lm (2700K) - 64lm (6500K)

69lm (2700K) - 77lm (6500K)

IP65

450mm

750mm

1000mm

08

£214.50

£251.50

£277.50



Garletta Connected by WiZ



- Dual purpose WiZ embedded garden spotlight supplied with wall mounting bracket and spike suitable for coastal areas
- Create the ambience of your choice with 16 million colours, as well as warm to cool white light (AGARLED/RGBTW/OCTOW)
- Tunable between 2700K 6500K via WiZ App and voice control (AGARLED/TW/OCTOW)
- Polycarbonate construction suitable for coastal areas
- Pre-wired with 2 metres of rubber insulated cable
- Please consider WiFi signal strength for this product





INPUT	HERTZ	TEMP	LIFETIN	ie (HRS)	CRI	SDCM B	EAM ANGLE	CLASS	IP
220/240V	50Hz	-20°C to 45°C	L80 5	4,000	Ra 80	6	100 [°]	2	IP65
CODE		DESCRIPTION	WATTAGE	CCT		LUMENS		LM/W	TRADE
AGARLED/RGBTW/C	OCTOW	RGB Tunable White	6.5W	2700-6500K (I	RGB) 45	50lm (2700K) - 500lm (6500l	K) 69lm (27	00K) - 77lm (6500K)	£118.00
AGARLED/TW/OCTO	W	Tunable White	6.5W	2700-6500	K 45	50lm (2700K) - 500lm (6500l	K) 69lm (27	00K) - 77lm (6500K)	£113.00

57

Warrington: +44 (0) 1942 433333 Belfast: +44 (0) 2890 773750

OCTO Powered by Casambi

OCTO Powered by Casambi provides professional level control coupled with easy intuitive commissioning. Ideal for any given commercial/ industrial application that requires wireless intelligent control. Casambi technology forms a proprietary Bluetooth mesh network. This mesh network does not have central resource or single point of failure.

58

- Easy to use, wireless controllable lighting system
- Intuitive operation and set-up via a smart device
- No need for an external gateway device
- Automatically forms a fast-wireless mesh network
- Nearby OCTO Powered by Casambi devices are clearly seen and added.
- Device firmware can be updated over the air
- Cloud services enhances user experience
- Smart lighting control switches can be easily added to the OCTO Powered by Casambi system
- OCTO App is compatible with some key dimming and colour control commands for the Philips Hue system

Pairing and Networks



Pairing: OCTO App will automatically find all OCTO enabled luminaires that are switched on

Grouping: Control luminaires in a group together or as individual fittings

Scenes: Lighting scenes and schedules create the perfect ambience for different occasions and needs **Network:** The established network is a mesh network, a mesh network does not have a central resource or point of failure.

59

Presence and Absence Detection

OCTO provides professional level control coupled with easy, intuitive commissioning. Functionality such as presence and absence detection - which reduces the amount of time the light is on. This can be set up effortlessly through the OCTO by Casambi App.

Absence Detection (Commercial)



Upon entering a room the person switches on the light as normal, but on leaving the detector switches off the lighting automatically. Lights can also be switched off manually

Daylight Harvesting

Presence Detection (Commercial)



Detectors will switch on lighting automatically when a person enters the room and switches off lighting automatically when no movement is detected

Daylight harvesting systems allow buildings to maximise natural lighting in the home/workplace, thereby reducing and increasing the artificial lighting as and when needed providing reduced energy consumption.

OCTO Smart PIR sensors can be used for Daylight harvesting to maximise energy savings

OCTO Wireless Emergency Lighting System

Revolutionary wireless connectivity for emergency luminaires via a self-healing Bluetooth mesh network. It is a requirement that emergency lighting systems should be tested and maintained at regular intervals in accordance with the latest regulations. This requires monitoring, testing and the logging of data all of which can be time-consuming and costly. The OCTO Wireless Emergency Lighting System offers a fully automatic and tailored approach to traditional emergency luminaire testing. The system can automatically check emergency lighting at preconfigured testing schedules and records the condition of each individual luminaire in the wireless network in real time.

Once commissioned, the emergency luminaires operational data is collected and can be turned into daily, weekly or monthly reports all viewed and controlled on an intuitive dashboard or interrogated at any time. You can also receive notifications should there be any results of the self-test devices that require attention.

Please enquire with a member of the sales team for more info

60

A

Control from anywhere

"Alexa, set presentation mode"

Your OCTO Gateway gives you the power to control your lighting remotely at the tap of an app.

Illuminate your office to welcome visitors, assist delivery drivers or level up your security, wherever you are in the world.

Seamless integration

- As well as native Alexa features, the OCTO Casambi gateway allows you to connect your Casambi lighting to a range of other smart devices.
- Including WiZ Connected, Ring, Hive and SamsungSmartthings


For example when your Ring doorbell detects motion during nighttime, your exterior lights can come on and stay for 10 minutes and then switch off. WIZ ring





OCTO Gateway Powered by Casambi

- Intuitive OCTO Smart Connected Gateway, opening the door to a world of connectivity across all of your IOT devices and solutions suitable for commercial and industrial applications
- Voice control for your Casambi lighting; offering hands-free controls
- Connects to a range of Smart devices; including WiZ Connected, Ring, Hive and SamsungSmartthings
- Voice control with Alexa, Hey Google and Siri Shortcuts
- Automate lighting routines and timers for hassle free control
- Control your lighting wherever you are with remote access
- Seamlessly integrate your whole Casambi network into hundreds or thousands of smart products
- Requires wired internet connection
- Supplied complete with RJ45 ethernet cable and mains BS1363 plug-top power supply



5YR









OUTPUT	INPUT	HERTZ	TEMP	CLASS	IP	
5V dc 2.1 Amp	100/240V	50/60Hz	0 to 25°C	2	IP20	
CODE		DI	ESCRIPTION		TRADE	
AOCTO/GATEWAY	OCTO Powered by Casambi Gateway £385					

CONNECTED LIGHTING

OCTO Indoor Controller Powered by Casambi

- Bluetooth enabled internal smart controller for use with the OCTO Casambi eco-system suitable for commercial and industrial applications
- Push-fit loop-in, loop-out terminals for ease and speed of installation
- Screw-less design
 - Compatible with all other bluetooth OCTO Casambi devices as part of the OCTO Casambi ecosystem
 - Intuitive fast operation from a smart lighting App
 - Future proofed free software and firmware updates
 - Can be used to control a group, sub groups or individual luminaires
 - Settings easily commissioned by a smart device

Please refer to instructions for further details.


App commissioning includes full control, dimming, scene setting and pre-set timer

** NB The indoor and outdoor OCTO Controllers are designed to operate Triac dimmable LED luminaires and LED light sources, however consideration must be given to PFC (Power Factor Correction) which can affect the final loading.

 Bluetooth wireless mesh ensures reliable and fast operation. Range between devices:15m internal, 30m external**















Installation Method

CODE	DESCRIPTION	OUTPUT	INPUT	HERTZ	CLASS	IP	TRADE
AOCTO/IC/50	Smart Indoor Controller	150W	220V-240V	50/60Hz	1	IP20	£173.00
AOCTO/IC/200	Smart Indoor Controller	200W	220V-240V	50/60Hz	1	IP20	£225.00

** Range is dependent on surroundings and obstacles, such as walls and building materials. **

* Circuit 1 - OCTO Indoor Controller Powered by Casambi

2

- Allows full control of all fittings connected to the network
- Scene setting to create a fitting atmosphere
- Holiday mode settings
- Compatible with indoor wireless smart switch
- Easy installation / retrofit ready

* Circuit 2 - OCTO Indoor Controller Powered by Casambi

- Turn on/off, dim or *adjustable colour temperature
- Timer functionality with built in sunrise and sunset app setting
- Control from anywhere depending on Wi-Fi connection

*Colour temperature may only be adjusted with compatible Smart Lamps/Luminaires

1 Circuit = 1 Controlle

9:41 Group


Gallery

Edit

1. Aller

OCTO Indoor CCT/RGBW Controller Powered by Casambi

- Bluetooth enabled internal CCT/RGBTW smart controller for use with OCTO Casambi eco-system and suitable for residential and commercial applications
- 12-24V bluetooth smart controller
- Compatible with all other bluetooth OCTO Casambi devices as part of the OCTO Casambi ecosystem
- Option to use externally within a waterproof enclosure
- Timed colour alert or changes for different daily events
- Initial start up provides the user with options for RGBW, RGB, Tunable White and single colour
- Shared/common positive output with 4 negatives outputs allow for 4 channel control
- App commissioning includes full control, dimming, scene setting and pre-set timer
- Settings easily commissioned by a smart device via the OCTO app
- Bluetooth wireless mesh ensures reliable and fast operation. Range between devices: 15m internal, 30m external**
- 12-24V constant voltage LED driver: AD30W/12V, AD75W/12V, ADK15W/24V, ADK60W/24V, ADK120W/24V
- Compatible with Krait, Boa, Adder and Cobra LED strip p234-p243





30

00000





Wiring Configuration for RGB




12-24VDC Power supply Wiring Configuration for 1-4 Separate white channels



12-24VDC Power supply

CODE	DESCRIPTION	MAX WATTAGE	OUTPUT	INPUT	CLASS	IP	TRADE
AOCTO/RGBW/BTC	Smart Single CCT/RGBW Controller	72W - 12V 144W - 24V	6A Max	12-24VDC	3	IP20	£235.00

65





** Range is dependent on surroundings and obstacles, such as walls and building materials. *





*Circuit 1 - OCTO indoor RGBW controller Powered by Casambi

- Scene setting to create a fitting atmosphere
- Compatible with all other Bluetooth OCTO devices

- Easy installation / retrofit ready
- Full RGBW colour palette via app
- Wireless colour synchronisation

Circuit = 1 Controller*

** Range is dependent on surroundings and obstacles, such as walls and building materials. **

1

66

- Control all fittings connected to this circuit
- Fast-wireless mesh network
- Security mode with pre-set timers
- IP65 bluetooth PIR sensor
- Scene setting to create an atmosphere to suit the occasion
- Dimmable 1% 100%

9:41 Group

Compatible with the outdoor wireless smart switch


Gallery

Edit

OCTO Outdoor Controller Powered by Casambi

- Bluetooth enabled internal outdoor smart controller for use with OCTO Casambi eco-system and suitable for residential and commercial applications
- Control outdoor lighting from smart device
- · Heavy duty screw connections suitable for SWA / outdoor cable types
- Compatible with all other bluetooth OCTO Casambi devices as part of the OCTO Casambi ecosystem
- Detachable connector block to aid connection of stronger cable types
- Waterproof with IP66 rating
- Robust polycarbonate casings for outdoor use. UV stabilised
- Intuitive fast operation from a smart app
- Can be used to control a group, sub groups or individual luminaires
- App commissioning includes full control, dimming, scene setting and pre-set timer
- Bluetooth wireless mesh ensures reliable and fast operation. Range between devices: 15m internal, 30m external**














Wiring Configuration

CODE	DESCRIPTION	OUTPUT	INPUT	HERTZ	CLASS	IP	TRADE
A0CT0/0C/IP65/200	Smart Outdoor Controller	200W	220V-240V	50/60Hz	1	IP66	£263.00


OCTO Indoor Wireless Architectural Smart Switch Powered by Casambi

- Bluetooth enabled internal smart switch for use with OCTO Casambi eco-system and suitable for residential and commercial applications
- Double rocker wireless wall switch
- High grade technopolymer construction available in 3 finishes:- white, metallic and black
- Electro-dynamic energy generator, maintenance free
- Compatible with all other bluetooth OCTO Casambi devices as part of the OCTO Casambi ecosystem
- Range within one room up to 10 metres line of sight
- Double-sided mounting film enclosed screwing onto a flat surface
- Double rocker with medial position, pressed/released





Powered by CASAMBI



AOCTO/WS/W



Metallic



Black

CODE	DESCRIPTION	IP	TRADE
AOCTO/WS/W	Indoor Wireless Switch - White		£230.00
A0CTO/WS/M	Indoor Wireless Switch - Metallic	IP20	£230.00
AOCTO/WS/B	Indoor Wireless Switch - Black		£230.00




Warrington:	+44 (0) 1942 4	433333 Bel	fast: +44 (0)) 2890 773750

Indoor Wireless Switch

A0CT0/BT/WS

OCTO Indoor Wireless Smart Switch Powered by Casambi

- Bluetooth enabled internal smart switch for use with OCTO Casambi eco-system and suitable for residential and commercial applications
- Double rocker wireless wall switch
- Electro-dynamic energy generator, maintenance free
- Compatible with all other bluetooth OCTO Casambi devices as part of the OCTO Casambi ecosystem
- Range within one room up to 10 metres line of sight
- Double-sided mounting film enclosed screwing onto a flat surface
- Double rocker with medial position, pressed/released







CONNECTED LIGHTING

£151.00




IP20

OCTO Indoor Wireless Xpress Smart Switch Powered by Casambi

Bluetooth enabled internal smart switches for use with OCTO Casambi eco-system and suitable for residential and commercial applications

- Multifunctional 4 way bluetooth enabled smart switch
- Settings easily commissioned by a smart device via the OCTO app
- Compatible with all other bluetooth OCTO Casambi devices as part of the OCTO Casambi ecosystem
- Integrated magnets ensure easy attachment to mounting bracket . (mounting bracket supplied with switch)
- Range within one room up to 30 metres line of sight





AOCTO/XP/WS/B





3

AOCTO/XP/WS/W





4 Corner Preset Buttons

Used to control a group, sub groups or individual luminaires, recall scenes and recall animations



Dimming Buttons

Multi-gesture up and down dimming buttons allow user complete control over light levels

Multipurpose Buttons

Additional multipurpose buttons allow user to alter the colour temperature or the indirect/direct light ratio (on applicable fittings only)



Corner illumination indicates which preset button is active


CODE	DESCRIPTION	IP	TRADE
AOCTO/XP/WS/W	Indoor Wireless Switch - White	IP20	£360.00
AOCTO/XP/WS/B	Indoor Wireless Switch - Black	IP20	£360.00

OCTO IP65 Wireless Smart Switch Powered by Casambi

Bluetooth enabled external smart switch for use with OCTO Casambi eco-system and suitable for residential and commercial applications

- . Wireless soft outdoor remote control
- Compatible with all other bluetooth OCTO Casambi devices as part of the OCTO Casambi ecosystem .
- Magneto-resistive power source .
- Spill and shock resistant .
- Advantages of a wireless system, no batteries required maintenance free .
- Integrated magnet allows it to be stuck on any metallic area .
- Range 30 metres











CODE	DESCRIPTION	IP	TRADE
AOCTO/BT/WS/IP65	Outdoor Wireless Switch	IP65	£97.00




OCTO Wireless Push to Make Switch Interface Powered by Casambi




Bluetooth enabled internal smart 4 channel push to make switch interface for use with OCTO Casambi eco-system and suitable for residential and commercial applications

- Bluetooth enabled smart 4 channel push to make switch interface
- Unit retrofits into existing push switch, making it smart enabled
- Compatible with all other bluetooth OCTO Casambi devices as part of the OCTO Casambi ecosystem
- Slim 15mm profile suitable for installation into 35mm recessed pattress
- Pre-wired ensuring a fast and easy installation into pre-existing wall switch
- Compact housing allows installation into pre-existing wall box so no additional work is required
- 3V lithium battery operated negating the requirement for mains wiring
- Can be used to control a group, sub groups or individual luminaires on a 1-4 button push switch
- Settings easily commissioned by a smart device via the OCTO app








Connection Diagram

Wires connected to the external push buttons. We suggest to keep the wires long enough, so battery replacement is possible without disconnecting the push buttons



Battery Replacement

When battery indicator is showing a low level, a new battery will be needed. (Battery is available as spare part).

Remove the cover (1) from the box (2). Pull out the PCB (3) slowly until the battery (4) can be removed. Replace battery and assure it is locked before sliding the PCB back in and putting the lit cover on.

AOCTO/SR 4 Channel Push to Make Switch Interface IP20 £260.0	CODE	DESCRIPTION	IP	TRADE
	A0CTO/SR	4 Channel Push to Make Switch Interface	IP20	£260.00

73

*1)

*))

Controller to Lighting Setup Connect OCTO indoor/outdoor controller Powered by Casambi to current lighting setup

*))

*))

*))

Controller to Lighting Setup Connect OCTO indoor/outdoor controller Powered by Casambi to current lighting setup

Consumer Unit to Controller Connect live cable from consumer unit to Connect OCTO indoor/ outdoor controller Powered by Casambi

Turn your switches into


Smart Switches

The 4 channel push to make switch interface retrofits into existing push switches, making them smart enabled (up to 4 gang push to make switches only). See above how the interface will integrate into your current switch setup.





OCTO Smart PIR Sensors Powered by Casambi

- Bluetooth enabled surface and recessed smart PIR sensors for use with OCTO Casambi eco-system and suitable for commercial applications
- Compatible with all other bluetooth OCTO Casambi devices as part of the OCTO Casambi ecosystem
- Infrared PIR detector and photocell
- Suitable for residential and commercial applications
- Loop-in, loop-out internal connections for ease of installation
- Detection range strength: 1) Strong detection zone i.e. person moving arm or walking towards PIR
 2) Secondary detection zone i.e. person walking perpendicular to PIR



AOCTO/BT/PIR-S





For optimum coverage recommended mounting height: 2.4m to 5m



Indoor Recessed PIR Sensor AOCTO/BT/PIR-R





Indoor Surface PIR Sensor AOCTO/BT/PIR-S

CODE	DESCRIPTION	INPUT	HERTZ	CLASS	IP	TRADE
A0CT0/BT/PIR-R	Smart Recessed PIR Sensor - White	0001/	501	0	1000	£236.00
AOCTO/BT/PIR-S	Smart Surface PIR Sensor - White	230V	50Hz	2	IP20	£296.00

OCTO IP65 Smart PIR Sensor Powered by Casambi

- Bluetooth enabled surfaced external smart PIR sensors for use with the OCTO Casambi eco-system suitable for commercial and industrial applications.
- Compatible with all other bluetooth OCTO Casambi devices as part of the OCTO Casambi ecosystem
- Suitable for residential and commercial applications
- Infrared PIR detector and photocell
- Detection range strength:
 - Strong detection zone(5m) i.e. person walking towards PIR
 Secondary detection

zone (10m, 8m) i.e. person walking perpendicular to PIR



🗲 20mm

threaded entry

spout

75



For optimum coverage recommended mounting height: 1m to 2.2m








CODE	DESCRIPTION	INPUT	HERTZ	CLASS	IP	TRADE
AOCTO/BT/PIR/IP65-S	Smart IP65 Surface PIR Sensor - Black	230V	50Hz	2	IP65	£327.00




OCTO IP66 Smart High Bay Racking Aisle PIR Sensor Powered by Casambi

- Bluetooth enabled IP66 smart highbay sensor for use with the OCTO Casambi eco-system suitable for racking aisle warehouse applications.
- Compatible with all other bluetooth OCTO Casambi devices as part of the OCTO Casambi ecosystem
 Infrared PIR detector and photocell
- Suitable for industrial high bay racking aisle applications with high
- mounting points (up to 20 metres)
- Fast and easy commissioning via the App

Mounting height up to 20m Perspective view ceiling mounted





5YR



CODE	DESCRIPTION	INPUT	HERTZ	TEMP	IP	CLASS	TRADE
A0CT0/BT/PIR/IP66/HBSP	Smart IP66 High Bay PIR Sensor - Racking Aisle	220-240V	50Hz	-20°C to 40°C	IP66	2	£385.00






CONNECTED LIGHTING

OCTO IP66 Smart High Bay Open Area PIR Sensor Powered by Casambi




CONNECTED LIGHTING

- Bluetooth enabled IP66 smart highbay sensor suitable for use with OCTO Casambi eco-system suitable for open area warehouse applications
- Compatible with all other bluetooth OCTO Casambi devices as part of the OCTO Casambi ecosystem Infrared PIR detector and photocell
- Suitable for industrial high bay open area applications with high mounting points (up to 14 metres)
- Fast and easy commissioning via the App



Up to 28m diameter









CODE	DESCRIPTION	INPUT	HERTZ	TEMP	CLASS	IP	TRADE
AOCTO/BT/PIR/IP66/HBWD	Smart IP66 High Bay PIR Sensor - Open Area	220-240V	50Hz	-20°C to 40°C	2	IP66	£385.00

